
500 CFM Ventilator Power Pack



SPECIFICATION SHEET

SY-HV-500SS POWER PACK



FEATURES

- Durable, 430 stainless steel with #4 brushed finish
- Non-exposed housing made with electrogalvanized steel
- Multi speed control
- Centrifugal blower, 500 CFM, 8.0 Sones
- 6" round duct connector/backdraft damper
- Accepts two halogen lamps, Type JC 12V 20W G4 Base (lamps included)
- Two washable filters with stainless steel covers, aluminum inner mesh, and quick-release latches
- Fully enclosed bottom
- One Year Limited Warranty
- Recommended for use with Models LB30, LB36, LT30, and LT36 Liners

OPTIONAL ACCESSORIES:

• Disposable charcoal filter kit - part no. B08999053

SPECIFICATIONS

VOLTS	AMPS	CFM	SONES	DUCT
120	2.8	500	8.0	6-in. round





TYPICAL SPECIFICATION

Power Pack shall be Broan® Model PM500SS.


(Castlewood model SY-HV-500SS)

Power Pack shall have a multi-speed fan switch and separate light switch.

Fan must be convertible between ducted and nonducted discharge. Ducted mode uses a washable aluminum mesh filter. Non-ducted mode uses optional, disposable charcoal filter.

Air delivery to be at least 500 CFM and sound levels not greater than 8.0 Sones.

Unit shall be UL and cUL listed.





HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in a state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.

Broan-NuTone LLC Hartford, Wisconsin www.broan.com 800-558-1711 Broan-NuTone Canada Mississauga, Ontario www.broan.ca 877-896-1119

