400 CFM Ventilator Power Pack





The PM400SS built-in powerpack insert offers you a custom appearance while protecting cabinetry with stainless steel liners. Featuring a smooth, stainless steel surface that is easy to clean with quick-release dishwasher-safe filter. The bright LED lighting enhances your cooking experience.


SIZE	STAINLESS	GREAS	e filter (i	replacem	ent) N	ON-DU	CTED FIL	TERS		
21-3/8 in. PM400SS		S99	S99010400 (Aluminum)			S99010464 (Charcoal)				
HVI PERFO	RMANCE									
Duct Orientation		Size	Damper	Sones			CFM			
				Normal	Medium	High	Normal	Medium*	High 0.25 in. w.g.	High 0.1 in. w.g.
Vertical - Rec	tangular	3¼ x 10 in.	Included	1.0	3.0	6.0	130	210	380	400
Horizontal - R	Rectangular	3¼ x 10 in.	Included	1.0	3.0	5.5	120	220	370	400
Round - Vertical		6 in.	Included	1.0	2.0	6.0	120	210	370	390

Max. Blower CFM**	450				
Control type	3-Speed Rotary Switch				
Delay off	no				
Filter Clean Reminder	no				
Heat Sentry™	yes				
ADA Capable	no				
_ighting	1-level LED (2 LED modules included)				
Grease Filter	Micromesh (Qty. 1)				
Installation Hardware	Included				
ENERGY STAR®	yes				
Recirculation	Non-ducted kit sold separately				
AC INPUT					
120 V, 60 Hz - 2.3 A	MPS				
OPTIONAL ACCESS	ORIES				
Stainless Steel Liners	LB30SS, LB36SS				
Non Duct Kit	HARKPM21				
Power Cord Kit	HCK44 (U.S.A. only)				
Hybrid Baffle Filter	HPFBN1				
Make-up Air Dampers	MD6TU, MD8TU and MD10TU				
MOUNTING HEIGHT					
24 in. to 30 in. from c	ooktop to bottom of hood				
LIMITED WARRANT					





• Will accommodate ranges with up to 40,000 BTU output



Dimensions shown in inches.

Can be used to comply with LEED requirements.



www.castlewood.com